

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims

Claim 1 (Cancelled).

Claim 2 (Previously Presented): The drain of claim 8, wherein said frame securable end has a circular configuration.

Claim 3 (Original): The drain of claim 2, wherein said frame exposed end has a non-circular geometric configuration.

Claim 4 (Previously Presented): The drain of claim 3, wherein said frame exposed end has a rectangular configuration.

Claim 5 (Cancelled).

Claim 6 (Previously Presented): The drain of claim 3, wherein said frame exposed end comprises a seat, said grate being fixed to said seat.

Claim 7 (Cancelled).

Claim 8 (Currently Amended): A drain comprising:
a drain body defining a drain cavity;
a frame having a securable end received by said drain body and an exposed end, said frame securable end including a lip, said frame being rotatable relative to said drain body for adjusting the position of said frame exposed end;
a clamp for fixing said securable end of said frame to said drain body; and
a grate received by said exposed end of said frame, wherein said drain body comprises a ledge having a sloped surface, said frame securable end slidably engaging said

sloped surface of said ledge when said frame is rotated relative to said drain body, wherein said clamp comprises a clamp body having a protrusion for clamping at least a portion of said lip of said frame securable end between said protrusion and said drain body and wherein said clamp further comprises a fastener extending between the lip and an opening in the drain body and being threaded into said drain body.

Claims 9-12 (Cancelled).

Claim 13 (Previously Presented): The method of claim 17, wherein the frame has an exposed end having a geometric configuration, such that said step of positioning the frame comprises orienting the geometric configuration of the frame exposed end relative to the floor drain surroundings.

Claim 14 (Original): The method of claim 13, wherein the floor surroundings comprises floor tiles.

Claim 15 (Original): The method of claim 13, wherein the floor surroundings comprises walls.

Claim 16 (Cancelled).

Claim 17 (Previously Presented): A method of installing a floor drain comprising:

fixing a drain body in a floor;

positioning a rotatable frame on the drain body by rotating the frame relative to the drain body, thereby orienting the frame to a desired position relative to surroundings of the floor drain;

securing the rotatable frame to the drain body; and

positioning a grate in the frame, wherein said drain body comprises a ledge having a sloped surface, said frame slidably engaging said sloped surface of said ledge when said frame is rotated relative to said drain body, wherein the frame has a securable end having a

circular configuration that is received by the drain body wherein said securable end includes a lip and said securing step comprises clamping at least a portion of the lip of the securable end of the frame between a protrusion of a clamp body and the drain body and wherein said clamping comprises extending a fastener through the clamp body and between the lip and an opening in the drain body and threading the fastener into the drain body.

Claim 18 (Cancelled).

Claim 19 (Currently Amended): A drain comprising:

a drain body defining a drain cavity;

a frame having a securable end received by said drain body and an exposed end, said frame securable end including a lip lip, said frame being rotatable relative to said drain body for adjusting the position of said frame exposed end;

a clamp for fixing said securable end of said frame to said drain body; and

a grate received by said exposed end of said frame, wherein said clamp comprises a clamp body having a protrusion for clamping at least a portion of said lip of said frame securable end to said drain body, and wherein said clamp body comprises a sloped drain body engaging surface to provide a gap between a portion of said drain body engaging surface and said drain body and wherein said clamp further comprises a fastener extending between the lip and an opening in the drain body.

Claims 20-23 (Cancelled).

Claim 24 (Previously Presented): A drain comprising:

a drain body defining a drain cavity;

a frame having a securable end received by said drain body and an exposed end, said frame securable end including a lip, said frame being rotatable relative to said drain body for adjusting the position of said frame exposed end;

a clamp for fixing said securable end of said frame to said drain body; and

a grate received by said exposed end of said frame, wherein said drain body comprises a ledge having a sloped surface, said frame securable end slidably engaging said

sloped surface of said ledge when said frame is rotated relative to said drain body, wherein said clamp comprises a clamp body having a protrusion for clamping at least a portion of said lip of said frame securable end between said protrusion and said drain body and wherein said clamp further comprises a fastener extending beyond said frame securable end and said clamp body and being threaded into said drain body and wherein the fastener does not extend through the protrusion.